Skid-Steer Loaders / S510 Skid-Steer Loader

S510 Loader Specifications & Options

Review complete specs for the S510 skid-steer loader and compare them with other models.

Standard	Optional	N/A Not Applicable		Units	US

Bobcat S510

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	55 hp
Turbocharged Engine	✓

Performance

Rated Operating Capacity (ISO)	1,876 lb
Tipping Load	3754 lb
Operating Weight	6208 lb
Travel Speed	7.6 mph

Capacities

Fuel Tank	24.8 gal

Hydraulic System

System Relief @ Quick Couplers	3,550 psi
Auxiliary Std Flow	17.1 gal/min
Auxiliary High Flow	n/a

Dimension

Length	133 in
Length without Attachment	104.6 in
Length with Standard Bucket	133 in
Width	64.7 in
Width (with bucket)	68 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	114.5 in
Reach @ Maximum Height	17 in
Turning Radius	80 in
Wheelbase	42.6 in

Features

Toutures	
Joystick Control	✓
Air Conditioning	▽
Adjustable Seat	•
Backup Alarm	•
BICS System (Interlock)	•
Cab Enclosure	▽
Sound Option	▽
Cab Heater	▽
Operating Lights	•
Parking Brake	.
Radio	✓
Rear Window	.
Top Window	•
Lift-Arm Support	•
Seat Belt	-
Suspension Seat	•
Suspension Seat Two Speed Travel	N/A
	N/A
Two Speed Travel	
Two Speed Travel Deluxe Instrumentation	
Two Speed Travel Deluxe Instrumentation Engine Shutdown	✓
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning	
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option	✓ ✓ N/A
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics	✓ ✓ N/A
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics Spark Arrestor Muffler	✓ ✓ N/A
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics Spark Arrestor Muffler Bob-Tach Attachment System	N/A I
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics Spark Arrestor Muffler Bob-Tach Attachment System Power Bob-Tach	N/A V
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics Spark Arrestor Muffler Bob-Tach Attachment System Power Bob-Tach ACS (Switchable Controls)	N/A N/A
Two Speed Travel Deluxe Instrumentation Engine Shutdown Hydraulic Bucket Positioning High Flow Option Auxiliary Hydraulics Spark Arrestor Muffler Bob-Tach Attachment System Power Bob-Tach ACS (Switchable Controls) Ride Control	✓ N/A N/A N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.