

Skid-Steer Loaders / S70 Skid-Steer Loader

S70 Loader Specifications & Options

Review the complete list of S70 skid-steer loader specs and compare them with other models.

Standard

☒

Optional

N/A

Not Applicable

UnitsUS

Bobcat S70

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	23.5 hp
Turbocharged Engine	N/A

Performance

Rated Operating Capacity (ISO)	760 lb
Tipping Load	1520 lb
Operating Weight	2892 lb
Travel Speed	6.3 mph

Capacities

Fuel Tank	6.5 gal
-----------	---------

## Hydraulic System

System Relief @ Quick Couplers	3,000 psi
Auxiliary Std Flow	9.8 gal/min
Auxiliary High Flow	n/a

## Dimension

Length	75.6 in
Length without Attachment	75.6 in
Length with Standard Bucket	97.3 in
Width	35.5 in
Width (with bucket)	36 in
Height	71.4 in
Height with Operator Cab	71.4 in
Height to Bucket Hinge Pin	94.5 in
Reach @ Maximum Height	15.8 in
Turning Radius	58.7 in
Wheelbase	28.4 in

## Features

Joystick Control	N/A
Air Conditioning	N/A
Adjustable Seat	<input type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Parking Brake	<input type="checkbox"/>
Radio	N/A
Rear Window	<input type="checkbox"/>
Top Window	<input checked="" type="checkbox"/>
Lift-Arm Support	<input type="checkbox"/>
Seat Belt	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	N/A
Deluxe Instrumentation	N/A
Engine Shutdown	N/A
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	N/A
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	N/A
ACS (Switchable Controls)	N/A
Ride Control	N/A
Rear Hydraulics	N/A
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.