Compact Track Loaders / T62 Compact Track Loader

T62 Loader Specifications & Options

Review complete specs for the T62 compact track loader and compare them with other models.

Standard	Optional	N/A Not Applicable	Ur	Jnits	US

Bobcat T62 T4

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	68 hp
Turbocharged Engine	✓

Performance

Rated Operating Capacity (ISO)	2,150 lb
Operating Capacity (50% of Tip)	3071 lb
Tipping Load	6143 lb
Operating Weight	8612 lb
Travel Speed	7.2 mph
Travel Speed (2-speed option)	10.2 mph
Ground Pressure (Rubber)	5.64 psi

Capacities

Fuel Tank	28.3 gal

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min

Dimension

Length	135 in
Length without Attachment	107 in
Length with Standard Bucket	135 in
Width	66.2 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	114.5 in
Reach @ Maximum Height	23 in
Turning Radius	81.6 in
Length of track on ground	54.3 in
Track Width	12.6 in
Track Width - Optional	15.8 in

Features

Joystick Control	✓
Air Conditioning	✓
Backup Alarm	=
BICS System (Interlock)	=
Cab Heater	✓
Operating Lights	=
Suspension Seat	•
Two Speed Travel	▼
Deluxe Instrumentation	✓
Engine Shutdown	•
Hydraulic Bucket Positioning	▽
High Flow Option	▼
Auxiliary Hydraulics	=
Bob-Tach Attachment System	•
Power Bob-Tach	✓
ACS (Switchable Controls)	▽
Ride Control	✓
Horn	=

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.