Compact Tractors / CT4055 Compact Tractor

CT4055 Specifications & Options

See all the CT4055 tractor specs and compare with other compact tractor models.

Standard Optional N/A Not Applicable

Units US

	Bobcat CT4055 SST
Engine	
Emissions Tier (EPA)	Tier 4
Horsepower	50.3 hp
Displacement	111 in^3
Number of Cylinders	3
Gross HP	50.3 hp
Engine Model	3FT-TL4-U
RPM	2750

Performance

Operating Weight	3,745 lb
Travel Speed	17.5 mph
Travel Speed - Reverse	17.1 mph
3-Point Hitch	Category 1
3-pt Lift Control Type	Hydraulic Position Control System
Lift Capacity at 24" behind Lift Point	2,716 lb
Rear PTO System	Independent
Rear PTO - RPM	540
PTO HP	49.6 hp
Mid PTO - RPM	2000

Capacities

Fuel Tank	11.9 gal

Hydraulic System

Implement Hydraulic Flow	9.62 gal/min
Total Hydraulic Flow	14.1 gal/min
Steering Hydraulic Flow	4.94 gal/min

Drive System

Brake Type	Wet Multi Disc
Transmission Type	n/a

Dimension

Length	125.5 in
Width	70 in
Height	97.4 in
Ground Clearance	15.3 in
Turning Radius	8' 7"
Wheelbase	5' 11"
Front Tire Size	Front AG.(TURF, INDUSTRIAL) '8-16
Rear Tire Size	Rear AG.(TURF, INDUSTRIAL) '13.6-24

Loader Attachment

Loader Lift Height	8' 8"
Lift Capacity @ 500mm ahead of bkt pivot	1,795 lb
Bucket Width	5' 6"

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.