

## Compact Track Loaders / T66 Compact Track Loader

# T66 Loader Specifications & Options

Review the complete T66 compact track loader specs and compare them with other models.

■ Standard
☑ Optional
N/A Not Applicable

Units US

### Bobcat T66

## Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

## Performance

Rated Operating Capacity (ISO)	2,450 lb
Operating Capacity (50% of Tip)	3500 lb
Tipping Load	7000 lb
Operating Weight	8927 lb
Travel Speed	7.2 mph
Travel Speed (2-speed option)	10.2 mph
Ground Pressure (Rubber)	5.9 psi

## Capacities

Fuel Tank	28.3 gal
-----------	----------

## Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min

## Dimension

Length	134.9 in
Length without Attachment	107 in
Length with Standard Bucket	134.9 in
Width	67 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	120 in
Reach @ Maximum Height	36.7 in
Turning Radius	81.5 in
Length of track on ground	54.3 in
Track Width	12.6 in
Track Width - Optional	15.7 in

## Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	N/A
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.