Compact Tractors / CT2535 Compact Tractor

CT2535 Specifications & Options

See all the CT2535 tractor specs and compare with other models.

Standard	Optional	N/A Not Applicable		Units	US

Bobcat CT2535 HST

Engine

Emissions Tier (EPA)	Tier 4
Horsepower	34.9 hp
Displacement	111 in³
Number of Cylinders	3
Gross HP	34.9 hp
Engine Model	3F-TM(H)4
RPM	2750

Performance

Operating Weight	3,585 lb	
Travel Speed	14.4 mph	
Travel Speed - Reverse	10.1 mph	
3-Point Hitch	Category 1	
3-pt Lift Control Type	Hydraulic Position Control System	
Lift Capacity at 24" behind Lift Point	1,631 lb	
Rear PTO System	Independent	
Rear PTO - RPM	540	
PTO HP	29.4 hp	
Mid PTO - RPM	1988	

Capacities

Fuel Tank	9 gal
-----------	-------

Hydraulic System

otal Hydraulic Flow	11.4 gal/min
---------------------	--------------

Drive System

Brake Type	Wet Multi Disc
Transmission Type	n/a

Dimension

Length	120.9 in
Width	64 in
Height	91 in
Ground Clearance	12.3 in
Turning Radius	8' 9"
Wheelbase	5' 5"
Front Tire Size	Front AG.(TURF, INDUSTRIAL)7-16 (28 x 8.5-15/6, 27X8.5-15)
Rear Tire Size	Rear AG.(TURF, INDUSTRIAL)11.2-24 (41 x 14-20/4, 15-19.5)

Loader Attachment

Loader Lift Height	8' 4"
Lift Capacity @ 500mm ahead of bkt pivot	1,389 lb
Bucket Width	5' 0"

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.